



A WYO-BEN PRODUCT  
**HYDROGEL** NSF

**HYDROGEL**

**HYDROGEL**

A WYO-BEN PRODUCT  
**HYDROGEL** NSF

A WYO-BEN PRODUCT  
**HYDROGEL** NSF

**HYDROGEL**

**HYDROGEL**

A WYO-BEN PRODUCT  
**HYDROGEL** NSF

A WYO-BEN PRODUCT  
**HYDROGEL** NSF

A WYO-BEN PRODUCT  
**HYDROGEL** NSF

A WYO-BEN PRODUCT  
**HYDROGEL** NSF

A WYO-BEN PRODUCT  
**HYDROGEL** NSF

NSF

A WYO-BEN PRODUCT  
**HYDROGEL** NSF



**HYDROGELL**<sup>®</sup>

ONE OF THE QUALITY  
WYO-BEN PRODUCTS



**WYOMING BENTONITE**

**FOR OIL WELL DRILLING**

**50 LBS./22.7 KG**

**WYO-BEN, INC., BILLINGS, MONTANA 59103**





## EZ-MUD<sup>®</sup> PLUS

High Molecular Weight Polymer Emulsion




**Health Hazardous Drilling Products**  
 Halliburton Energy Services, Inc. (HES)  
 P.O. Box 1674, Houston, TX 77262  
 HES Technical Services: 1-877-276-2432 or 281-471-4813  
 Emergency Telephone: 281-571-5888

May cause eye, skin, and respiratory irritation.  
 May cause headache, dizziness, and other central nervous system effects.  
 May be harmful if swallowed.

**Use and Storage:** See MSDS, Section 9, for handling, use, and storage information. Store in a cool, dry place. Do not use if the container is damaged or if the contents are solid. Do not use if the contents are solid. Do not use if the contents are solid. Do not use if the contents are solid.

**First Aid:** If inhaled: Remove person to fresh air. If irritation persists, seek medical attention. If swallowed: Drink water. Do not induce vomiting. If on skin: Wash with soap and water. If in eyes: Flush with water for 15 minutes. Seek medical attention if irritation persists.

**Environmental:** Do not discharge into the environment. Do not discharge into the environment. Do not discharge into the environment. Do not discharge into the environment.

**Disposal:** Dispose of in accordance with local, state, and federal regulations. Dispose of in accordance with local, state, and federal regulations. Dispose of in accordance with local, state, and federal regulations.

**Compatibility:** Compatible with most drilling fluids. Compatible with most drilling fluids. Compatible with most drilling fluids.

Water Treatment	Product	Quantity per Gallon
Water Treatment	Product	Quantity per Gallon
Water Treatment	Product	Quantity per Gallon
Water Treatment	Product	Quantity per Gallon
Water Treatment	Product	Quantity per Gallon

**NET CONTENTS:**  
 19 L = 5 Gallons  
 19 KG = 42 Pounds

**HALLIBURTON S123E1**

## EZ-MUD<sup>®</sup> PLUS

High Molecular Weight Polymer Emulsion




**Health Hazardous Drilling Products**  
 Halliburton Energy Services, Inc. (HES)  
 P.O. Box 1674, Houston, TX 77262  
 HES Technical Services: 1-877-276-2432 or 281-471-4813  
 Emergency Telephone: 281-571-5888

May cause eye, skin, and respiratory irritation.  
 May cause headache, dizziness, and other central nervous system effects.  
 May be harmful if swallowed.

**Use and Storage:** See MSDS, Section 9, for handling, use, and storage information. Store in a cool, dry place. Do not use if the container is damaged or if the contents are solid. Do not use if the contents are solid. Do not use if the contents are solid. Do not use if the contents are solid.

**First Aid:** If inhaled: Remove person to fresh air. If irritation persists, seek medical attention. If swallowed: Drink water. Do not induce vomiting. If on skin: Wash with soap and water. If in eyes: Flush with water for 15 minutes. Seek medical attention if irritation persists.

**Environmental:** Do not discharge into the environment. Do not discharge into the environment. Do not discharge into the environment. Do not discharge into the environment.

**Disposal:** Dispose of in accordance with local, state, and federal regulations. Dispose of in accordance with local, state, and federal regulations. Dispose of in accordance with local, state, and federal regulations.

**Compatibility:** Compatible with most drilling fluids. Compatible with most drilling fluids. Compatible with most drilling fluids.



Water Treatment	Product	Quantity per Gallon
Water Treatment <td>Product <td>Quantity per Gallon</td> </td>	Product <td>Quantity per Gallon</td>	Quantity per Gallon
Water Treatment <td>Product <td>Quantity per Gallon</td> </td>	Product <td>Quantity per Gallon</td>	Quantity per Gallon
Water Treatment <td>Product <td>Quantity per Gallon</td> </td>	Product <td>Quantity per Gallon</td>	Quantity per Gallon
Water Treatment <td>Product <td>Quantity per Gallon</td> </td>	Product <td>Quantity per Gallon</td>	Quantity per Gallon

**NET CONTENTS:**  
 19 L = 5 Gallons  
 19 KG = 42 Pounds

**HALLIBURTON S123E1**

## EZ-MUD<sup>®</sup> PLUS

High Molecular Weight Polymer Emulsion

**Health Hazardous Drilling Products**  
 Halliburton Energy Services, Inc. (HES)  
 P.O. Box 1674, Houston, TX 77262  
 HES Technical Services: 1-877-276-2432 or 281-471-4813  
 Emergency Telephone: 281-571-5888

May cause eye, skin, and respiratory irritation.  
 May cause headache, dizziness, and other central nervous system effects.  
 May be harmful if swallowed.

**Use and Storage:** See MSDS, Section 9, for handling, use, and storage information. Store in a cool, dry place. Do not use if the container is damaged or if the contents are solid. Do not use if the contents are solid. Do not use if the contents are solid. Do not use if the contents are solid.

**First Aid:** If inhaled: Remove person to fresh air. If irritation persists, seek medical attention. If swallowed: Drink water. Do not induce vomiting. If on skin: Wash with soap and water. If in eyes: Flush with water for 15 minutes. Seek medical attention if irritation persists.

**Environmental:** Do not discharge into the environment. Do not discharge into the environment. Do not discharge into the environment. Do not discharge into the environment.

**Disposal:** Dispose of in accordance with local, state, and federal regulations. Dispose of in accordance with local, state, and federal regulations. Dispose of in accordance with local, state, and federal regulations.

**Compatibility:** Compatible with most drilling fluids. Compatible with most drilling fluids. Compatible with most drilling fluids.



Water Treatment	Product	Quantity per Gallon
Water Treatment <td>Product <td>Quantity per Gallon</td> </td>	Product <td>Quantity per Gallon</td>	Quantity per Gallon
Water Treatment <td>Product <td>Quantity per Gallon</td> </td>	Product <td>Quantity per Gallon</td>	Quantity per Gallon
Water Treatment <td>Product <td>Quantity per Gallon</td> </td>	Product <td>Quantity per Gallon</td>	Quantity per Gallon
Water Treatment <td>Product <td>Quantity per Gallon</td> </td>	Product <td>Quantity per Gallon</td>	Quantity per Gallon

**NET CONTENTS:**  
 19 L = 5 Gallons  
 19 KG = 42 Pounds

**HALLIBURTON S123E1**

## EZ-MUD<sup>®</sup> PLUS

High Molecular Weight Polymer Emulsion

**Health Hazardous Drilling Products**  
 Halliburton Energy Services, Inc. (HES)  
 P.O. Box 1674, Houston, TX 77262  
 HES Technical Services: 1-877-276-2432 or 281-471-4813  
 Emergency Telephone: 281-571-5888

May cause eye, skin, and respiratory irritation.  
 May cause headache, dizziness, and other central nervous system effects.  
 May be harmful if swallowed.

**Use and Storage:** See MSDS, Section 9, for handling, use, and storage information. Store in a cool, dry place. Do not use if the container is damaged or if the contents are solid. Do not use if the contents are solid. Do not use if the contents are solid. Do not use if the contents are solid.

**First Aid:** If inhaled: Remove person to fresh air. If irritation persists, seek medical attention. If swallowed: Drink water. Do not induce vomiting. If on skin: Wash with soap and water. If in eyes: Flush with water for 15 minutes. Seek medical attention if irritation persists.

**Environmental:** Do not discharge into the environment. Do not discharge into the environment. Do not discharge into the environment. Do not discharge into the environment.

**Disposal:** Dispose of in accordance with local, state, and federal regulations. Dispose of in accordance with local, state, and federal regulations. Dispose of in accordance with local, state, and federal regulations.

**Compatibility:** Compatible with most drilling fluids. Compatible with most drilling fluids. Compatible with most drilling fluids.

Water Treatment	Product	Quantity per Gallon
Water Treatment <td>Product <td>Quantity per Gallon</td> </td>	Product <td>Quantity per Gallon</td>	Quantity per Gallon
Water Treatment <td>Product <td>Quantity per Gallon</td> </td>	Product <td>Quantity per Gallon</td>	Quantity per Gallon
Water Treatment <td>Product <td>Quantity per Gallon</td> </td>	Product <td>Quantity per Gallon</td>	Quantity per Gallon
Water Treatment <td>Product <td>Quantity per Gallon</td> </td>	Product <td>Quantity per Gallon</td>	Quantity per Gallon

**NET CONTENTS:**  
 19 L = 5 Gallons  
 19 KG = 42 Pounds

**HALLIBURTON S123E1**



# EZ-MUD® GOLD

Clay/Shale Stabilizer



**Baroid Industrial Drilling Products**  
Product Service Line, Halliburton  
P.O. Box 1678, Houston, TX 77251  
Customer Service: 1-877-575-7413 or 281-871-4813  
Emergency Telephone: (281) 875-8000

**Warnings:**  
• May cause eye and skin irritation  
• Airborne dust may be explosive

Product	Net Weight	Net Volume
50 lb (22.7 kg)	50.00	44.34
100 lb (45.4 kg)	100.00	88.68
200 lb (90.9 kg)	200.00	177.36
500 lb (227.3 kg)	500.00	443.40
1000 lb (453.6 kg)	1000.00	886.80

NET CONTENTS: 100 LB (45.4 kg)

HALLIBURTON

S010F1

# EZ-MUD® GOLD

Clay/Shale Stabilizer



**Baroid Industrial Drilling Products**  
Product Service Line, Halliburton  
P.O. Box 1678, Houston, TX 77251  
Customer Service: 1-877-575-7413 or 281-871-4813  
Emergency Telephone: (281) 875-8000

**Warnings:**  
• May cause eye and skin irritation  
• Airborne dust may be explosive

Product	Net Weight	Net Volume
50 lb (22.7 kg)	50.00	44.34
100 lb (45.4 kg)	100.00	88.68
200 lb (90.9 kg)	200.00	177.36
500 lb (227.3 kg)	500.00	443.40
1000 lb (453.6 kg)	1000.00	886.80

NET CONTENTS: 100 LB (45.4 kg)

HALLIBURTON

S010F1